



MOL Plc.
DS MOL

MOL_0713_012 / 2

VG 32

Printed: 5/7/2021

SAP product number		13004596	
Combined Nomenclature		27101999	
Property	Unit	Standard	Requirement
Apperance at 25 °C		Visual appearance	Transparent, sediment free
Density at 15 °C	g/cm3	EN ISO 12185	Report
Viscosity at 40 °C	mm2/s	EN ISO 3104	28.00 - 35.00
Viscosity at 100 °C	mm2/s	EN ISO 3104	Report
Viscosity index		MSZ ISO 2909	min. 100
Flash Point by Cleveland	C_fok	EN ISO 2592	min. 210
Pour Point	C_fok	ISO 3016	max. -15
MCR	%(m/m)	EN ISO 10370	max. 0.02
Water Content	%(m/m)	MSZ EN ISO 9029	max. 0.025
Colour (ASTM)		MSZ ISO 2049	max. 1.0
TAN	mgKOH/g	ISO 6618	max. 0.02
Air Release at 50 °C	perc	MSZ 2044	Report
Volatility Loss by Noack	%(m/m)	ASTM D 5800 B	max. 12.0
Time of Deemulsibility at 54 °C	perc	MSZ ISO 6614	Report
Sulphur Content	%(m/m)	EN ISO 8754	max. 0.03
CA	%	ASTM D 2140	Report
PCA	%(m/m)	IP 346	max. 2.9

Remark :